# **PRODUCT INFORMATION**



## **ANTICORIT BML 3**

Mineral oil-free corrosion preventive

### Description

ANTICORIT BML 3 is a fully synthetic, mineral oil-free corrosion preventive, functional fluid and assembly fluid formulated for all systems which need to be protected with mineral oil-free products such as hydraulic and brake systems. Complies with FMVSS 116-DOT 4 and DOT 3 and SAE J 1703.

### Application

ANTICORIT BML 3 is ready-to-use and can be applied by spraying, dipping or by filling the equipment so that all surfaces are wetted. All areas to be protected must be sufficiently covered.

#### **Benefits**

- Reliable corrosion protection
- Fully synthetic
- Special vapour phase inhibitors

#### **Storage conditions**

If sealed in the original container ANTICORIT BML 3 can be stored up to 36 months at temperatures between - 20 and + 40  $^{\circ}$ C.

The indication of a minimum period of storage does not include any guarantee of durability.



PI 3-4143e, Page 1, PM 3, 18.04.2013

# **PRODUCT INFORMATION**



## **ANTICORIT BML 3**

Mineral oil-free corrosion preventive

### Typical chemical and physical properties:

Property	Unit	Data	Test method
Colour		0.5	DIN ISO 2049
Density at 15 ℃	kg/m³	0.985	DIN 51 757
Viscosity at 40 °C	mm²/s	40	DIN 51 562-1
Flashpoint	C	> 200	DIN ISO 2592
Pourpoint	C	- 42	DIN ISO 3016
Corrosion Protection Data Condensation climate	cycles	> 12	LUCAS condensation test *)

\*) 1 cycle = 16h; 46°C; 95% relative humidity 8h; 21°C; 95% relative humidity on original brake components

PI 3-4143e, Page 2, PM 3, 18.04.2013

# **PRODUCT INFORMATION**



## **ANTICORIT BML 3**

Mineral oil-free corrosion preventive

The information contained in this product information is based on the experience and know-how of FUCHS EUROPE SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application.

We therefore recommend that you consult a FUCHS EUROPE SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning. With the publication of this product information, all previous editions cease to be valid.

Any form of reproduction requires express prior written permission from FUCHS EUROPE SCHMIERSTOFFE GMBH.

© FUCHS EUROPE SCHMIERSTOFFE GMBH. All rights reserved.

PI 3-4143e, Page 3, PM 3, 18.04.2013