# **PRODUCT INFORMATION**



## PLANTOGEL 2 N

Grease Based on Rape Seed Oil Environmentally Friendly and Rapidly Biodegradable

### Description

PLANTOGEL 2 N is an environment-friendly grease based on calcium soap and renewable, rapidly biodegradable rape seed oil.

The combination of rape seed oil and anhydrous calcium soap is a perfect supplement of thickener and base oil with regard to temperature capability and range of application. Calcium soap is toxicologically safe.

PLANTOGEL 2 N has excellent lubricating properties and offers wear protection.

PLANTOGEL 2 N is water resistant, has an excellent adhesive capacity and protects against corrosion.

### Application

PLANTOGEL 2 N is recommended for all relubricating points requiring conventional NLGI 2 greases. It is suitable for grease nipples, as total loss lubrication in agriculture and forestry, and as open gear lubrication in case of water or soil contamination, i.e. lock gates, sewage treatment plants, grease points and, lifting devices, chains, bolts, open gears, tow couplings, garage doors, battery terminals etc.

#### Attention!

Do not use PLANTOGEL 2 N for wheel hubs, universal shafts and hot water pumps. Do not mix PLANTOGEL 2 N with other greases.

#### Advantages

- Good corrosion protection
- Good water resistance
- Strongly adhesive
- Good wear protection

### Shelf Life

The minimum shelf life is 12 months if the product is properly stored between  $0^{\circ}$  and  $40^{\circ}$  in its unopened original container in a dry place. The indication of a minimum shelf life does not include any guarantee of durability.



PI 5-8110e, Page 1/3, PM 5, 08/10

Telefon: +49 621 3701-0 Telefax: +49 621 3701-570 E-Mail: zentrale@fuchs-europe.de

# **PRODUCT INFORMATION**



## PLANTOGEL 2 N

### Grease Based on Rape Seed Oil Environmentally Friendly and Rapidly Biodegradable

#### **Characteristics**

Properties	Unit	Value	Test method
Classification	-	KX 2 C-20	DIN 51 502
Colour	-	light brown	-
Thickener	-	calcium soap	-
Dropping point	Ĵ	>110	IP 396
Worked penetration (Pw 60)	0,1 mm	265 - 305	DIN ISO 2137
Oil separation 18h / 40°C	%	< 1,5	DIN 51 817
Rust inhibiting properties Emcor Test	degree of corrosion	0 - 0	DIN 51 802
Base oil	-	rape seed oil	-
Temperature range short term	Ç	-20 to +70 +90	DIN 51 825

PI 5-8110e, Page 2/3, PM 5, 08/10

# **PRODUCT INFORMATION**



### PLANTOGEL 2 N Grease Based on Rape Seed Oil Environmentally Friendly and Rapidly Biodegradable

The information contained in this product information is based on the experience and know-how of FUCHS EUROPE SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application.

We therefore recommend that you consult a FUCHS EUROPE SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning. With the publication of this product information, all previous editions cease to be valid.

Any form of reproduction requires express prior written permission from FUCHS EUROPE SCHMIERSTOFFE GMBH.

© FUCHS EUROPE SCHMIERSTOFFE GMBH. All rights reserved.

PI 5-8110e, Page 3/3, PM 5, 08/10