



TITAN SYN SN SAE 0W-20

Super High Performance, high fuel-economy oil for a variety of gasoline engines in passenger cars. Good cold starting behaviour and low oil consumption.

Description

TITAN SYN SN SAE 0W-20 is an advanced, SAE 0W-20 all-season engine oil specially formulated for gasoline engines providing very high fuel efficiency. Smooth cold start behaviour and fast engine lubrication is another advantage of TITAN SYN SN SAE 0W-20. With its high temperature high shear viscosity of 2.6 mPas TITAN SYN SN SAE 0W-20 perfectly services modern gasoline engines of many vehicle manufacturers.

Application

TITAN SYN SN SAE 0W-20 Shall be used predominantly for cars of American and Asian vehicle manufacturers in naturally aspirated and turbo-charged gasoline engines without extended drain intervals. TITAN SYN SN SAE 0W-20 offers safe operation at all running conditions.

TITAN SYN SN SAE 0W-20 is miscible and compatible with conventional branded engine-oils. However, intermixtures with other engine oils should be avoided in order to fully utilize the product's benefits. Respectively a complete oil change is recommended when converting to TITAN SYN SN SAE 0W-20. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

Advantages/Benefits

- For use in normally aspirated and turbocharged gasoline engines.
- Very good viscosity-temperature behaviour and high shear stability ensure all-season suitability even at severe operating conditions
- Reliable cold starting and rapid oil circulation
- Very good wear protection
- Protects against engine sludge.
- Low oil consumption
- High fuel efficiency according API SN resource conserving

Specifications

- API SN
- ILSAC GF-5

Approvals

- -

FUCHS Recommendations

- -



TYPICAL CHARACTERISTICS

Density at 15 °C	DIN 51757	0,848 g/ml
Colour	DIN ISO 2049	232 ASTM
Flash Point, CoC	DIN ISO 2592	-39 °C
Dynamic Viscosity at - 25°C	DIN 51398	5900 mPas
Dynamic Viscosity at 150°C	CEC	2,6 mPas

PI60559e, PMA, 05.02.2014, Page 2



The information contained in this product information is based on the experience and know-how of FUCHS EUROPE SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pretreatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application.

We therefore recommend that you consult a FUCHS EUROPE SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid.

Any form of reproduction requires express prior written permission from FUCHS EUROPE SCHMIERSTOFFE GMBH.

© FUCHS EUROPE SCHMIERSTOFFE GMBH. All rights reserved.